



series 2200

CHEMICAL INJECTION PUMPS




PRODUCT FEATURES

- 1/4 horsepower motor is available in TENV or Explosion Proof, single or three phase
- The stroke adjustment is adjustable while running
- Fluid ends are 316 stainless steel
- Four plunger sizes are available; 3/16", 1/4", 3/8", and 1/2"
- The geared motor has a built in gear reducer available in 15, 30, 60 strokes per minute
- Maximum volume of 130 gallons per day (duplex model)
- Maximum discharge pressure 1,000 PSI
- Modular design allows easily interchangeable fluid ends
- Motors meet CSA and UL specifications
- Oil-less-requires minimal lubrication for long life

OPTIONS

- Ceramic plungers which provide longer packing life

MODEL DESIGNATION



IndustrialZONE.com™
 Your Portal to the Industrial World

IndustrialZone
 P.O. Box 667306
 Houston, Texas 77266
 United States

(713)-395-1508
 Fax: (713) 893-6924
 support@industrialzone.com
www.industrialzone.com



Series 2200 with 1/4 HP Motor			
Model Number	Plunger Size	SPM	Maximum GPD @ 1000 PSI
2204	3/16"	15	2.19
		30	4.37
		60	8.74
2201	1/4"	15	3.84
		30	7.68
		60	15.36
2203	3/8"	15	8.64
		30	7.28
		60	34.56
2205	1/2"	15	15.36
		30	30.72
		60	61.44

PARTS LIST				
ITEM	B/P NO.	NO REQD.	NAME	MATERIAL
1	TB1483	1	COVER	ASTM A48 C.I.
2	TA0136	4	1/4-20 x 3/4 THUMBSCR	CAD PL. C.STL.
3	TA5963	1	GASKET COVER	NITRILE
4	TC2048	1	HOUSING	ASTM A48 C.I.
5	TA0142	5	HHCS 5/16-18 x 1.25	CAD PL. C.STL
6	TA0144	5	NUT, HEX 5/16-18	CAD PL. C.STL
7	TA0300	3	CUT WASHER 5/16	CAD PL. C.STL
8	TB1492	1	BASE PL. SIMPLEX	GALV.STL.
9	TB1472	1	3/16 SS LP HEAD ASS'Y	316 SST
	TB1557		1/4 SS LP HEAD ASS'Y.	316 SST
	TB1558		3/8 SS LP HEAD ASS'Y	316 SST
	TB1559		1/2 SS LP HEAD ASS'Y	316 SST
10	TA5953	1	DRIVE CLIP	STEEL
11	T31542	1	CROSS HEAD	AISI 4140 HR STL
12	TA5823	1	ECCENTRIC CAM	C 1018 STL.
13	TA5830	1	ROLLER BEARING	STEEL
14	TA5831	1	10-24UNC x 1/4 ST.SCR	STEEL
15	TA6386	1	KEY	STEEL
16	TA5832	2	SLEEVE BEARING	NYLON
17	TA5826	1	SHAFT GUARD	PVC
18		1	GEAR MOTOR	
19	TA0139	4	HHCS 3/8-16 x 1.25	CAD PL. C.STL.
20	TA0439	4	NUT, HEX 3/8-16	CAD PL. C.STL.
21	TA0459	4	LOCKWASHER 3/8 REG	CAD PL. C.STL.
22	TA0746	4	WASHER, 3/8 FLT	CAD PL. C.STL.
23	TA5822	1	STROKE ADJUSTER	C1213 C.R.S.
24	TA5824	1	LOCK NUT STROKE ADJ.	416 SS
25	TA2825	1	ADJUSTING SCREW	416 SS
26	TA3964	1	CROSS HEAD BEARING	INJHOLD NYLON
27	TA5965	1	CROSS HEAD BEARING	INJHOLD NYLON
28	TA5966	1	VENT SCREEN	SS
29	TC2126	1	BRACKET	CS ZINC PLT
30	TA2585	1	BUMPER	PLASTIC HOSE

